

## ROUND HEATED SPECIFICATIONS

## RTR08 - Standard 240V model

MIRROR POLISHED AND SATIN BRUSHED MANUFACTURED FROM 304 GRADE STAINLESS STEEL

COLOURED FINISHES MANUFACTURED FROM 201 GRADE STAINLESS STEEL IP55 RATED (COLOURED FINISHES ARE IP54 RATED)

ALL TOWEL RAILS AVAILABLE WITH EITHER BOTTOM LEFT OR RIGHT OUTPUT

ALL STANDARD RAILS ARE DUAL PURPOSE, OFFERING A PLUG AS STANDARD, BUT PACK CONTAINS A HARD WIRING KIT

CAN BE MOUNTED UPSIDE DOWN


10 YEAR WARRANTY FOR CONSTRUCTION / HEATING ELEMENT

COATING ON COLOURED RAILS ARE COVERED BY A 2 YEAR WARRANTY

· Cable length: 1.4m, plug included

the complete range: radiantheating.com.au

 To see our range of low voltage (12V) models please refer to our website for



FEATURES	CODE	SIZE (MM)	FINISH	
Round bar / Height 750mm / 7 evenly spaced bars / 125W  (Display 1, 120M)	RTR08LEFT	900x750	Polished	
	RTR08RIGHT	900x750	Polished	
(Black rail 130W)  • Standard model is 240V / IP55 rated	BRU-RTR08LEFT	900x750	Satin Brushed	
<ul> <li>Vertical bars 32mm diameter</li> </ul>	BRU-RTR08RIGHT	900x750	Satin Brushed	
Horizontal bars 19mm diameter	BRTR08LEFT	900x750	Matt Black	
• 112mm from wall	BRTR08RIGHT	900x750	Matt Black	