5.

6.

7.

8.

Glass

90 min

Rapid

Prewash

 $645 \times 645 \times 871$ 

845\*



# 60cm Freestanding Dishwasher

# Black Stainless Steel

AESTHETICS
Black Stainless Steel Finish
Touch Controls with LED Display
FUNCTIONALITY
Capacity: 15 Place Settings
8 × Wash Programs inc. Auto Wash
Auto Open Drying
Adjustable, Height-lift Top Basket
Third-layer Cutlery Drawer
Stainless Steel Tub & Base
1–24hr Delay Start
Half Zone, Extra Clean & Express Wash
70° C Max Water Temperature
Triple stage Filtration
BLDC Inverter Motor

AESTHETICS	
Black Stainless Steel Finish	
Touch Controls with LED Display	
FUNCTIONALITY	
Capacity: 15 Place Settings	
8 × Wash Programs inc. Auto Wash	
Auto Open Drying	
Adjustable, Height-lift Top Basket	
Third-layer Cutlery Drawer	
Stainless Steel Tub & Base	
1–24hr Delay Start	
Half Zone, Extra Clean & Express Wa	sh
70° C Max Water Temperature	
Triple stage Filtration	
BLDC Inverter Motor	

AESTHETICS
Black Stainless Steel Finish
Touch Controls with LED Display
FUNCTIONALITY
Capacity: 15 Place Settings
8 × Wash Programs inc. Auto Wash
Auto Open Drying
Adjustable, Height-lift Top Basket
Third-layer Cutlery Drawer
Stainless Steel Tub & Base
1–24hr Delay Start
Half Zone, Extra Clean & Express Wash
70° C Max Water Temperature
Triple stage Filtration

FUNCTIONS	
	1. Auto Wash
	2. Intensive
	3. Heavy
	4. ECO
	SIZE, W/D/H (MM)
	Packaged
	Physical
	Door Opened 90°

Physical	598 × 600 ×
Door Opened 90°	1175
WEIGHT (KG)	
Net: 43.6	Gross: 47.9

CONSUMPTION	
Energy Rating (MEPS)	4 Stars
Water Rating (WELS)	5 Stars

MAX NOISE LEVEL	
44 dB(A) re 1 pW	

### INSTALLATION

Freestanding or Built-in		
Water Connection	Cold Water	
Length of Hose	1.8m	
Inlet / Drain	1.5m / 1.6m	
Water Pressure:	0.04-1.00MPa	

## SAFETY Child Lock Safety

AquaStop Overflow Protection

### **POWER REQUIREMENTS**

Supplied Plug	10 amp
Rated Voltage	220-240V
Rated Frequency	50Hz
Power Consumption	1760-2100W


### ADDITIONAL DETAILS

Barcode	9349260095694
Warranty	5 Years



#### **FRONT VIEW**

Note: Please refer to the user manual for detailed installation instructions



#### **DIMENSIONS (MM)**

A 598	B 600	* Hei
C 845*	D 1175	for

ight can be reduced to 815mm built-in installation